## **Town of Canton**

### Rec Park - River Field Scope of Work

# Rec Park - River Field Little League Ball Park

The applicant will utilize contracts for the repairs to the site to restore this facility "in-kind" to its pre-disaster design, function, and capacity within the existing footprint (see Exhibit 1). Some facilities will have mitigation applied.

## **Chain Link Fencing:**

- 1. Perimeter
  - a. Install 416 feet of 4-foot-high Galvanized Metal Knuckle Chain Link Fence.
  - b. Install 42 each of 6-feet long by 3-inch Diameter Galvanized Metal Post set in concrete 2-foot-deep underground.
  - c. Install 416 feet of 1.5-inch Diameter Galvanized Metal Top Rail.
  - d. Install 2 each, 4 FT wide x 5 FT high, of Galvanized Metal Gate with hardware.
  - e. Install 1 each, 8 FT wide x 5 FT high, of Galvanized Metal Double Gate with hardware.
- 2. Dugouts (rear 2 ea)
  - a. Install 30 feet of 5-foot-High Galvanized Metal Knuckle Chain Link Fence.
  - b. Install 8 each of 7-feet-Long by 3-inch Diameter Galvanized Metal Post set in concrete 2-foot-deep underground.
  - c. Install 30 feet of 1.5-inch Diameter Galvanized Metal Top Rail.
- 3. Dugouts (front 2 ea)
  - a. Install 14 feet of 8-foot-high Galvanized Metal Knuckle Chain Link Fence.
  - b. Install 3 each of 10-feet-high by 3-inch Diameter Galvanized Metal Post set inch concrete 2-foot-deep underground.
  - c. Install 14 feet of 1.5-inch Diameter Galvanized Metal Top Rail.
- 4. Backstop
  - a. Install 54 feet of 16-foot-high Galvanized Metal Knuckle Chain Link Fence.
  - b. Install 6 each of 20-feet-long by 3-inch Diameter Galvanized Metal Post set inch concrete 3-foot-deep underground.
  - c. Install 54 feet of 1.5-inch Diameter Galvanized Metal Top Rail and 4 mid-rails.
- 5. Backstop Top
  - a. Install 16 feet of 8-foot-high Galvanized Metal Knuckle Chain Link Fence secured to top of backstop at 45 degrees over home plate.
  - b. Install 3 each of 8-feet-long by 3-inch Diameter Galvanized Metal Post attached to top of backstop.
  - c. Install 16 feet of 1.5-inch Diameter Galvanized Metal Top Rail and 1 mid-rail.
  - d. Install 2 each of 12-feet-long by 1.5-inch Diameter Galvanized Metal Diagonal Top Rail.
  - e. Install 12-feet-long by 8-foot-high triangular section of Galvanized Metal Knuckle Chain Link Fence secured to top of backstop at 45 degrees over home plate.

## **Bleachers:**

1. Install 3 each of 15 feet long, 5 Platform/row metal Bleachers.

### Field:

1. Install 175 Cubic Yards of clay infield.

- 2. Install 3 each of 1st, 2nd, 3rd Rubber Bases, 12-inch-long x 12 inch wide, within the infield.
- 3. Install 1 each of Rubber Home Base, 17-inch square with two of the corners removed so that one edge is 17-inches long, two adjacent sides are 8.5-inches, and the remaining two sides are 12-inches and set at an angle to make a point.

# Dugouts (2 ea):

- 1. Install 14 feet by 14 feet cantilever pyramid fabric shade cover on single mast
- 2. Provide 14-feet-long by 7-inch-wide aluminum metal Bench.

## **Concession/Storage Building:**

- 1. Provide 1 each of Pre-assembled Portable Wood Building with two 4-feet wide x 3-feet high windows and composition shingles, 12 feet long x 8 feet wide x 9 feet high.
- 2. Provide 1 each of portable generator with 4-110 Volt Single Outlets.

## Parking Lot:

1. Remove and replace 117.4 Cubic Yards of Gravel Surface, 169 feet long x 75 feet wide x 0.25 feet deep.

**Engineers Estimate: \$125,000** 

#### **Directions**

Submissions must be sent in the form of a bid with the envelope labeled "Request for Proposal - Town of Canton Aquatics Center Flood Gate Installation" to 85 Summer Street by 2:00 p.m. Eastern Time (EST) on May 2, 2025. Proposals must contain the signatures of company representatives who are authorized to execute documents on behalf of the firm.

Bid will be awarded to the lowest responsive bidder.

The Town of Canton accepts no responsibility for any expense related to preparation or delivery of proposals.

Exhibit 1 – River Field Park

